



1.866.940.0696
sm@shoemakermfg.com

Combination Fire/Smoke Damper Order Form

MODEL: CFSD, FSD

Date :
Distributor:
Contact:

Branch:
Phone:

Quote #:
Job/Reference
Email:

Quantity	Style		Model	Class	Sleeve (Standard 18", 20 gauge)	Sleeve Style	Actuator	Other Options			
	W	H						(a)	(b)	(c)	(d)

Size:
Class 1: min. 12w x 8h, max. 36x36
Class 2: min. 8x8, max. 36x36

Model:
FSD111 - (1 1/2 hour fire/smoke, vertical or horizontal)
CFSD222 - (1 1/2 hour corridor fire/smoke, horizontal only)
SD333 - Smoke damper, vertical and horizontal)

Leakage Class: (must specify)
Class I (ultra-low leakage)
Class II (Standard low leakage)

Sleeve Style:
Standard 18", 20 gauge

Sleeve Style:
A - Square or rectangular (standard)
C - Rectangular with flange
D - Square with round collar (ex. 10x10-8 or 8x8-6)

Actuator:

- 120V
- 24V
- Pneumatic

Other Options:
A - Factory installed *Innovair* Photoelectric (photo) duct smoke detector (min. sleeve 25")
B - Retaining angles
C - Factory installed model 6600 10x6 access door (min. sleeve 25")
D - Internal mounted actuator (min. dmaper 8x8 on 25" sleeve)
Note: Fusible link standard on internal mount actuator

ALL COMBINATION FIRE/SMOKE DAMPERS ARE SPECIAL ORDER AND NOT RETURNABLE
We cannot quote this order without all columns completed. Lead time for this product is approximately 12-15 working days. Expedited Service available. Cost not included in quote. See price book for shipping options.