


Commercial Submittal

45° Aluminum Lattice Filter Grille

MODEL: 645FG







Standard Features:

- 1/2" x 1/2" x 1/2" 45° sightproof aluminum lattice, deflection parallel to longest dimension
- · Hinged removable extruded aluminum face frame with signature line marks
- · Hinges parallel to longest side
- · Face set in an outer filter grille frame
- Hand operated lever for easy filter access
- 4-way reversible door on square sizes
- 2-way reversible door on rectangular sizes
- · Concealed mounting holes with mounting screws
- Holds up to a 1" filter (not included) with filter retention tabs (645FG1)
- · Rust resistant pre-coat with durable powder finish
- · Soft White

Options:

2" Filter capacity (645FG2)

4" Filter capacity (645FG4)

 $\mbox{${\gamma}_2$" x ${\gamma}_2$" x ${\gamma}_2$" 45° sightproof aluminum lattice deflection parallel to shortest dimension (646FG1/646FG2)$

Alternative hinge and latch options – Filter Grille Order Supplement on website




Soft White
Driftwood Tan





645FG1 Frame Detail



Product Notes:

Filter grilles are manufactured 3/16" undersized nominal duct (outside dimension) for ease of installation. Air filter should be ¼" to ½" undersized. Verify with air filter manufacturer for air specification to ensure a proper fit.

Shoemaker filter grilles allow for installation of larger thickness filters (we offer 2" and 4" filter depths on specific models) which can reduce pressure drop on the overall system, improving air flow through the heat exchanger and allowing more time between filter changes. Contact customer service for more information.

Additional Information:

Submittal Notes

Project / Location:
Engineer:
Architect:
Contractor: