

# **Commercial Submittal**

Drum Louver - Single Vane

MODEL: DL (also DL2, DL-DA, DL-GO)

#### **Standard Features:**

- High Capacity Cylindrical Drum
- Engineered for high capacity, long throw applications such as sports arenas, gymnasiums, conference centers, industrial plants and other large spaces
- Flexibility to change throw direction and spread of the discharge jet
- Made from extruded aluminum

#### **Options:**


Dual flow configuration for dividing air flow through adjustable vanes (DL2) Damper available (DL-DA) Gang operator (DL-GO)

## Finishes:


STANDARD COLORS


OPTIONAL FINISHES: (EXTRA CHARGE)


Clear Anodized Satin Silver White Black



Drum Louver







| Dimensions (in inches)   |        |        |    |    |    |      |        |           |     |        |    |    |     |         |         |    |    |    |    |         |         |     |     |    |    |    |    |    |    |       |    |    |    |    |  |  |  |
|--------------------------|--------|--------|----|----|----|------|--------|-----------|-----|--------|----|----|-----|---------|---------|----|----|----|----|---------|---------|-----|-----|----|----|----|----|----|----|-------|----|----|----|----|--|--|--|
| AVAILABLE LISTED HEIGHTS |        |        | 6" |    |    |      |        |           | 10" |        |    |    |     |         | 12"     |    |    |    |    |         |         |     | 15" |    |    |    |    |    |    |       |    |    |    |    |  |  |  |
| Available I<br>Width     |        | 9      | 12 | 18 | 24 | 30   | 36     | 48        | 60  | 20     | 25 | 30 | 35  | 40      | 50      | 60 | 70 | 20 | 25 | 30      | 35      | 40  | 50  | 60 | 70 | 15 | 20 | 25 | 30 | 40    | 48 | 50 | 60 | 70 |  |  |  |
| Number of L              | ouvers | 2      | 3  | 5  | 7  | 9    | 11     | 15        | 19  | 3      | 4  | 5  | 6   | 7       | 9       | 11 | 13 | 3  | 4  | 5       | 6       | 7   | 9   | 11 | 12 | 2  | 3  | 4  | 5  | 7     | 9  | 9  | 11 | 13 |  |  |  |
|                          | Α      |        |    |    | 13 | 3/4" |        |           |     | 2 5/8" |    |    |     |         |         |    |    |    |    |         | 3       | "   |     |    |    |    |    |    | 3  | 3 1/2 | "  |    |    |    |  |  |  |
|                          | В      |        |    |    | 43 | 3/8" |        |           |     |        |    |    | 6 1 | /8"     | '       |    |    |    |    |         | 6 1     | /8" |     |    |    |    |    |    |    | 8"    |    |    |    |    |  |  |  |
|                          | 3 1/2" |        |    |    |    |      | 5 7/8" |           |     |        |    |    |     | 6 1/4"  |         |    |    |    |    |         | 9 1/2"  |     |     |    |    |    |    |    |    |       |    |    |    |    |  |  |  |
|                          | D      | 3"     |    |    |    | 5"   |        |           |     |        |    |    | 5"  |         |         |    |    |    |    | 5"      |         |     |     |    |    |    |    |    |    |       |    |    |    |    |  |  |  |
|                          | Е      | 8 1/2" |    |    |    |      |        | 12 1/4"   |     |        |    |    |     | 13 7/8" |         |    |    |    |    | 16 7/8" |         |     |     |    |    |    |    |    |    |       |    |    |    |    |  |  |  |
|                          | F      | 7"     |    |    |    |      |        | 10 13/16" |     |        |    |    |     |         | 12 1/2" |    |    |    |    |         | 15 1/2" |     |     |    |    |    |    |    |    |       |    |    |    |    |  |  |  |

### **Additional Information:**

Submittal Notes

| Project / Location: |  |
|---------------------|--|
| Engineer:           |  |
| Architect:          |  |
| Contractor:         |  |