

Fire Rated Submittal


U.L. Fire Resistance Classified 3 Cone T-Bar Diffuser MODEL: HVL-FR Series



Standard Features:

- T-Bar FR assembly includes 2750 Series Ceiling Radiation Damper and TTB Series Thermal Blanket
- UL listed fire resistance T-Bar
- 3 hour rated fire resistance rating
- Building materials rated 3 hours or less
- 3 cone steel diffuser with hinged core for easy duct access
- Designed for high volume air delivery
- Delivers supply air in a 360° air pattern
- 2" ADC compliant round collar with bead for ease of installation
- Collar sizes available in 6", 7", 8", 9", 10", 12", 14", & 16"
- Rust resistance pre-coat with durable powder finish
- Soft White





Finishes: STANDARD COLORS	DESIGNER COLORS	
☐ Soft White ☐ Driftwood Tan	■ Black ■ Bronze ■ Storm Gray ■ Cement Gray	Aluminum Paint Coffee Tan Warm White Glossy White

Maximum Product Height		
DAMPER SIZE	HEIGHT (A)	
6"	6 1/2"	
7"	7"	
8"	7 1/2"	
9"	8"	
10"	8 1/2"	
12"	9 1/2"	
14"	10 1/2"	
16"	11 1/2"	



Additional	Information:
------------	--------------

Submittal Notes Project / Location:

Engineer: Architect: Contractor: