

Performance Data



201 Series

Size	Eff. Area	Velocity	300		400			500			600			700			800			900			1000		
		Duct Pt	0.006		0.01			0.015			0.021			0.029			0.038			0.048			0.065		
6x6	0.187	CFM	56		75			93			112			131			149			168			187		
		NC	<20		<20			20			20			25			30			30			35		
		Throw	4	4.5	5.5	5	5.5	6.5	6	7	9	6	7.5	11	7	8.5	12	8	9.5	13	9	10.5	16	9	11
8x4	0.172	CFM	52		69			86			103			120			137			155			172		
		NC	<20		20			20			25			30			30			35			35		
		Throw	3	3.5	4.5	5	5.5	6.5	6	6.5	7.5	6	7	9	7	7.5	11	8	9.5	13	8	9.5	15	9	11
8x6	0.258	CFM	77		103			129			155			180			206			232			258		
		NC	<20		20			20			25			30			30			35			40		
		Throw	4	4.5	5.5	6	6.5	7.5	6	7	9	7	8.5	12	8	10	14	10	12	16	10	12	18	11	13.5
8x8	0.343	CFM	103		137			172			206			240			275			309			343		
		NC	<20		20			25			25			30			35			35			40		
		Throw	5	5.5	6.5	6	7	9	7	8	10	8	9.5	13	10	12	16	11	13.5	18	13	15	22	13	16
10x4	0.202	CFM	61		81			101			121			141			161			182			202		
		NC	<20		20			25			25			30			35			35			40		
		Throw	4	4.5	5.5	5	5.5	6.5	6	7	9	7	7.5	11	8	9.5	13	9	11	15	10	12	18	11	13
10x6	0.303	CFM	91		121			151			182			212			242			272			303		
		NC	<20		20			25			25			30			35			40			40		
		Throw	4	4.5	5.5	5	6	8	7	8	10	8	9.5	13	9	11	15	11	13	17	11	13.5	20	13	15
10x10	0.504	CFM	151		202			252			302			353			403			454			504		
		NC	<20		20			25			25			30			35			40			40		
		Throw	6	6.5	7.5	7	8	10	9	11	13	11	13	17	12	14.5	20	14	17	23	15	18	28	16	20
12x4	0.249	CFM	75		100			125			149			174			199			224			249		
		NC	<20		20			25			25			30			35			40			45		
		Throw	4	4.5	5.5	6	6.5	7.5	7	8	10	7	8.5	12	8	10	14	10	12	16	10	12	18	12	14.5
12x6	0.374	CFM	112		149			187			224			261			299			336			374		
		NC	<20		20			25			30			30			35			40			45		
		Throw	5	5.5	6.5	6	7	9	8	10	12	8	10	14	10	12	16	12	14.5	20	12	14.5	22	14	17
12x12	0.747	CFM	224		299			374			448			523			598			672			747		
		NC	<20		20			25			30			35			35			40			45		
		Throw	7	8	10	8	10	12	12	13.5	17	13	15.5	21	15	18	24	17	21	28	18	22	32	19	24
14x4	0.296	CFM	89		118			148			178			207			237			267			296		
		NC	<20		20			25			30			35			40			40			45		
		Throw	4	4.5	5.5	6	6.5	7.5	8	9	11	8	9.5	13	9	11	15	11	13	17	11	13	19	13	15
14x6	0.444	CFM	133		178			222			267			311			355			400			444		
		NC	<20		20			25			30			35			40			45			45		
		Throw	6	6.5	7.5	7	8	10	8	9	11	9	11	15	11	13.5	19	13	15	21	13	16	24	15	18

Performance Data



201 Series

Size	Eff. Area	Velocity	300	400	500	600	700	800	900	1000
		Duct Pt	0.006	0.01	0.015	0.021	0.029	0.038	0.048	0.065
14x8	0.592	CFM	178	237	296	355	415	474	533	592
		NC	<20	20	25	30	35	40	45	<45
		Throw	6 7 9	8 9 11	10 11.5 15	11 13 17	12 14.5 20	15 17 23	15 18 28	16 20 30
14x14	1.037	CFM	311	415	518	622	726	829	933	1037
		NC	20	25	30	30	35	40	<45	<45
		Throw	8 10 12	11 12.5 16	13 16 20	15 18 24	17 21 29	18 23 31	20 26 38	22 29 43
16x16	1.374	CFM	412	550	687	824	962	1099	1236	1374
		NC	20	25	30	35	40	45	<45	<45
		Throw	9 11 13	12 13.5 17	14 17 21	16 19 25	18 22 30	19 24 32	21 27 39	23 30 44

Performance Notes:

- 1) Throw values are measured in feet for terminal velocities of 150/100/50 FPM
- 2) Throw data is based on supply air and room air both at isothermal conditions
- 3) Effective core areas listed in chart are defined as the measurement of space between the blades actually being utilized by the air
- 4) Data obtained from tests conducted in accordance with ANSI/ASHRAE standard 70-2006